



GC135-155VX

13,500 - 15,500 lb

ICE Cushion Tire Fork Lift

Built to be operator friendly.

Operator comfort is enhanced by the increased foot space in the well designed operator's compartment. The isolated powertrain reduces noise and vibration minimizing operator fatigue and increasing operator productivity throughout a shift. Enhanced operator visibility is available through the Yale® Hi-Vis™ mast. An optional cab is available with or without air conditioning.

The GC135-155VX offers a generous lineup of standard and optional features for operators to find their ideal position for comfort all shift long:



ADJUSTABLE STEER COLUMN

Innovative design helps accommodate operators of all sizes. The standard, cowl-mounted manual hydraulic control levers also allow easy access for right-side entry/exit.



REAR DRIVE HANDLE +

Optimally placed on the rear overhead guard leg, The rear drive handle (complete with horn button), creates a comfortable and secure work environment with an optional swivel seat.



LOW STEP HEIGHT

A low step height provides easy entry and exit. The overhead guard design also offers plenty of headroom with visibility even at higher fork heights.





ELECTRO-HYDRAULIC CONTROLS

The optional Yale* Accutouch electro-hydraulic control offers an enhanced ergonomic design with shorter reach and throw and considerably less effort required to operate versus common hydraulic levers. The fully-adjustable armrest is contoured for maximum comfort and flexibility to minimize muscle and joint strain.



Ultimate productivity.

The GC135-155VX series of trucks is available in several configurations to meet and exceed your material handling application requirements. The Veracitor® can be configured for standard, medium and heavy duty applications with state-of-the-art-features, enabling superior power for maximum performance.

Figine Type Fire! Type Fire! Type For Emissions Compliant For Emissions Compliant Service intervals Naintenance-free emissions Deep skirt engine block Air to air intercooler Replaceable exhaust valve seat inserts Turbo charged Air to air intercooler Replaceable exhaust valve seat inserts Diesel oxidation catalyst Selective Catalytic Reduction ISCR) system Maximum Productivity															, cem				
							Tout.	# Abore.	, ;	r heads				rat insert	seat inse			n (SCR) s	
					Service Compliant		Pance Tecl	Cast ire	nd cylinde	block		ler	e valve s	ust valve	der	atalyst	filter	c Reducti _i	(du
Уре	ę.	Wer			ssions Co.	rate or mervals	ex Perform	ance-free	n block ar	Turbo ch.	Paga.	Replaces L.	able inta	able exha	Diesel Cylinder	Diesel pridation catalyst	Selection Selection	Maximum Productivis.	
Engine Type	Fuel Type	Horsepower	Torque	EPA E	Service	Vale	Mainten :	Cast ire	Deep st.	Turbo ch.	Air to a	Replace	Replace intake valve so	4-Valva	Diesel	Diesel	Selection	Maximu	
Kubota 3.8L LPG	LPG	91 hp @ 2400 RPM	221 ft. lbs @1000 RPM	•	500	•	•	•	•			•	•	•				•	
Kubota 3.8L DOC	Diesel	74 hp @ 2200 RPM	227 ft. lbs @1400 RPM	•	500		•	•	•	•	•	•	•	•	•				



KUBOTA 3.8L LPG



KUBOTA 3.8L DOC DIESEL

Two transmission selections are available: the Electronic Powershift and the Techtronix 332 transmission.

Both transmissions feature smooth inching, electronic shift control and neutral start/brake interlock.

- The standard Electronic Powershift features two forward speeds and two reverse speeds with hydraulic inching.
- The optional **Techtronix 332 transmission** features three-speeds forward and two-speeds reverse for additional travel speed and gradeability, controlled ramp descent (limiting roll to three inches per second), electronic inching (requires no adjustment), and the Auto Deceleration System, bringing the unit to a complete stop when the accelerator pedal is released. Tire spin is reduced by precisely regulating engine speed during controlled power reversals.
 - + = Optional equipment



DID YOU KNOW?

54% of companies list meeting customer demands for faster response times as one of their top five challenges? Moving materials more efficiently can hel save time and boost productivity.



Low cost of operation.

The purchase price of a truck is only a small part of its overall cost. A lift truck's cost of ownership is the largest portion of dollars spent and includes such elements as periodic maintenance, unscheduled repairs, tires, brakes and fuel costs. The Yale engineers focused on cost savings with additional engine and transmission options, world-class serviceability and dependability.

INTELLIX VSM – The smart vehicle system manager, maximizes uptime by monitoring and protecting key truck functions.

SIMPLIFIED SERVICEABILITY – Minimize maintenance costs associated periodic maintenance and unscheduled repairs with easy access to key components and reduced service requirement.

AUTO DECELERATION SYSTEM – This system automatically slows the truck when the throttle pedal is released, minimizing brake usage requirements, and reducing costs associated with brake wear. Available with the optional Techtronix transmission.

WET DISC BRAKES – The oil-cooled, wet disc brakes are fully sealed against contamination making them ideal for tough environments. These long life brakes help minimize maintenance costs associated with the truck.



Veracitor® VX series versatility

Recognizing that no two environments are exactly alike, Yale gives you the option of tailoring your lift truck's performance and features to your application. In addition to engine and transmission choices, the innovative Yale® Flex Performance Technology™ (available with LPG only) offers selectable performance modes that provide the flexibility to maximize fuel economy or productivity to match application needs. No matter what truck configuration you choose, you can depend on the Veracitor® series lift truck.

The Techtronix 332 transmission offers improved tire savings through controlled power reversals. All three engine options deliver outstanding fuel economy with competitive performance, reducing operating costs.



Engines

Kubota 3.8L LPG

Power = 91 hpTorque = 221 lb. ft @ 1000 RPM

Kubota 3.8L DOC Diesel

Power = 74 hpTorque = 227 lb. ft. @ 1400 RPM

Transmissions

Electronic Powershift

Two speeds forward Two speeds reverse Heavy duty clutch packs Hydraulic inching Electronic shift control

Techtronix 332 +



Three speeds forward Two speeds reverse All features of electronic powershift Controlled rollback Controlled power reversal Auto deceleration system Electronic inching Higher top speed

Hydraulics

Cowl-mounted mechanical levers

Easy reach ergonomic design Excellent right-side access

Accutouch electro-hydraulic controls +

Fingertip activation Excellent right-side access

+ = Optional equipment

Ultimate

dependability.

Yale Veracitor® VX trucks are designed and manufactured to be among the most dependable trucks in the industry today. Yale's rugged powertrain offers durability with computer-controlled engine and transmissions, robust clutch packs and stronger gears and shafts. An optional powertrain protection system and enhanced monitoring increases longterm durability.

Rugged powertrain

- Filtration system
- Sealed electrical connectors
- · Combi-cooler radiator

Hall effect sensors

Reliable electronics

The Veracitor® VX offers reliable electronics, including sealed connectors, allowing the entire truck to be pressure washed. Hall Effect sensors and switches in the key switch and direction lever have solid state components that are magnetically operated and are 100% sealed from the environment. O-ring face seals on all high pressure hydraulic connections eliminate pipe fittings and the need for thread sealants creating leak-free joints. A superior filtration system increases the life span of all hydraulic components.

Innovative cooling system

The innovative cooling system design on the Veracitor® VX trucks enables dramatically lower operating temperatures than competitive models. The system offers excellent airflow through optimized ducting and high-volume tunnels allowing our trucks to run significantly cooler and longer. Radiators are 100% shockmounted for long life. The standard combi-cooler radiator has a four-row aluminum core radiator and a four-row externally mounted heavy duty transmission oil cooler for tough applications. Radiators for diesel engines feature air to air intercooler technology for additional engine power and efficiency.



The radiator lint screen helps prevent debris from clogging the radiator. The easy access design allows the operator to quickly clean any accumulated debris.



Radiator features air to air intercooler technology



Excellent air flow



EZ-Tank Bracket +

The optional EZ-Tank Bracket swings out and drops down approximately 60 degrees for virtually effortless removal and installation of the LPG tank.

+ = Optional equipment



Simply at your

service.

Not only is the Veracitor® VX series designed to require less maintenance, it is also designed to be extremely easy to service. From the rear-opening, one-piece hood and on-board diagnostics, to the reliable, most comprehensive parts availability in the industry, these trucks were designed with service details in mind. The cowl-to-counterweight access makes servicing fast, easy and convenient.

Auto Deceleration System

The Auto Deceleration System feature (available with the optional Techtronix transmission) reduces brake usage, leading to decreased brake maintenance and pad replacement. All these contribute to reduce service costs and add to your bottom line. The standard electronic powershift transmission and the optional Techtronix 332 transmission both feature smooth electronic inching, requiring no periodic adjustment.



Cowl-tocounterweight access

The Veracitor® VX truck has a rear-opening, one-piece hood that opens 85 degrees.. Coupled with the one-piece floor plate, it provides excellent access. Easy to remove floor plate requires no tools and rear-opening hood offer complete access to the powertrain. Engine compartment daily checks are all located within close reach and are easily performed. The uncluttered layout under the hood offers clean hydraulic and electrical routings.

- Rear-opening, one-piece hood
- On-board diagnostics
- Advanced dash display
- · One-piece floor plate
- Clean hydraulic and electrical routings



About Yale®



Yale Materials Handling Corporation is one of the oldest manufacturers of lift trucks in the world. We've been in the business of lifting since 1875 and we apply that experience to help customers solve materials handling challenges. Our full line of lift trucks range in capacity from 2,000 to 36,000 pounds and are powered by internal combustion engines or electric options. Yale also offers robotic solutions, telemetry, fleet management, parts, financing and training. From traditional lift truck equipment to emerging technologies, our goal, every day, is to work with our nationwide dealer network to continually improve and provide the solutions you need, when and how you need them.

MATERIALS HANDLING FOR:



3PL



Auto Parts Distribution



Beverage



Cold & Frozen Foods



Food Distribution



Food Processing



Furniture & Furnishings



Health & Pharma



Home Centers



Printing & Publishing



Retail & E-Commerce

Yale Materials Handling Corporation

P.O. Box 7367 Greenville, NC 27835-7367 U.S.A.

www.yale.com

YALE, of and PEOPLE. PRODUCTS. PRODUCTIVITY. are trademarks, service marks or registered marks in the United States and certain other jurisdictions. © Yale Materials Handling Corporation 2021. All Rights Reserved.

Trucks may be shown with optional equipment. Truck performance may be affected by the condition of the vehicle, how it is equipped and the application. Specifications are subject to change without notice. Consult your Yale* Dealer if any of the information shown is critical to your application.

CERTIFICATION: Yale lift trucks meet the design and construction requirements of B56.1-1969, per OSHA Section 1910.178(a)(2), and also comply with the B56.1 revision in effect at time of manufacture. Classified by Underwriters' Laboratories, Inc.